ZOINKER.COM

How to use the Zoinker cutting guide to make NEW-CUTSHELLS

---Select Regular birdshot shell---

INSERT SHELL INTO ZOINKER if it seems loose and turns easily in the guide, use a ¼" strip of paper to shim between shell and inside of Zoinker.

Place Zoinker with enclosed shell onto cutting board on a flat side down.

--Cutting the Shell--

Using a utility knife or a razor-knife carefully cut through the hull via slot on R side from the front of the slot towards the cutting surface to make first slit.

Turn the zoinker with enclosed shell shell to the next side, make next cut.

Continue until all four sides of the shell hull has been cut, the cuts should be between the powder wad and the shot cup creating two pairs of cuts offset from each other by 90 degrees rotation and 3/16" along the length of the shell.

The front and back ends of the modified shell should be connected by 4 small sections of uncut hull.

-- Using the New -Cutshell --

Load your shotgun normally since the Zoinker guide produces cut-slugs which are mechanically stable for magazine loading.

The Zoinkerized shell becomes a frangible slug with improved ballistic performance. The Zoinker guide can be used to make matrix-stabilized shells also. Contact Us for instructions.

Support Nevada Wildlife, Shooting Sports and Our Constitutional Rights especially the Second Amendment.

Zoinker.Com Is a USA company, employing ONLY USA Citizens

Be Careful and enjoy shooting Zoinkerized shells.